

GeoVent® End Outlets

GAS VENTING SYSTEM

PRODUCT DESCRIPTION

GeoVent® End Outlets are designed for use with:

- GeoVent® active/passive gas venting systems

GeoVent® End Outlets are manufactured to meet or exceed the minimum average roll values listed below.

BENEFITS

- N/A

INSTALLATION

Product should be installed in accordance with specific installation guide specifications.

PACKAGING

- Sold individually

PHYSICAL PROPERTIES

CORE PROPERTIES	TEST METHOD	VALUE
Compressive Strength	ASTM D 1621	9,500 psf
Thickness	ASTM D 1777	1.0 in.
Flow Rate (Hydraulic gradient = .1)	ASTM D 4716	30 gpm/ft/width

FABRIC PROPERTIES	TEST METHOD	VALUE
A.O.S.	ASTM D 4751	70 US Sieve
Grab Tensile Strength	ASTM D 4632	100 lbs.
Puncture Strength	ASTM D 4833	65 lbs.
Flow Rate	ASTM D 4491	140 gpm/ft ²
Permeability	ASTM D 4491	0.21 cm/sec
Fabric - Mass / Unit Area	ASTM D 5261	4.0 oz/yd ²
UV Resistance	ASTM D 4355	70%

AVAILABILITY

Shipping available from two convenient plant locations:

- CETCO, 1001 S Linwood Ave, Santa Ana, CA
- CETCO, 218 NE Industrial Park Rd, Cartersville, GA

Contact your local technical sales manager at:
714-384-0111 or 800-527-9948

LIMITATIONS

- N/A